



Product Information 02.40.30

21-03-2014

Agrifluid CVT

Description

Agrifluid CVT is a modern, semi-synthetic, hydraulic and transmission oil for use in automatic CVT transmissions. The product is based on a mix of synthetic and solvent-refined base oils, combined with advanced additives. Agrifluid CVT features the following properties:

- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability
- Effective 'Extreme Pressure' and wear resistance
- Suitable for systems with wet brakes
- Outstanding resistance to rust and corrosion

Application

Agrifluid CVT is a combined transmission/hydraulic oil. The product has been specially developed for automatic CVT transmissions, which are being used more and more frequently in modern agricultural and/or forestry machinery.

Specifications

Massey Ferguson M1144/M1145	John Deere J20C	Massey Ferguson M1143
ZF TE-ML 06B/07B	Allison C4	

Typicals

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	6400
Viscosity 40 °C, mm ² /s	88,40
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	156
Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	10,9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Sulphate Ash, %

1,45

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.