



Product Information 02.40.10

21-03-2014

Agrifluid HT

Description

Agrifluid HT is a modern, universal hydraulic and transmission oil. It is based on solvent-refined base oils, combined with additives. Agrifluid HT features the following properties:

- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability
- Effective 'Extreme Pressure' and wear resistance
- Suitable for systems with wet brakes
- Outstanding resistance to rust and corrosion

Application

Agrifluid HT is a UTTO (Universal Tractor Transmission Oil), developed specially for everyday operating conditions in the agricultural industry. This universal oil has been developed as a lubricant oil for the hydraulic and transmission systems of the most common agricultural and earth-moving machines.

Specifications

API GL-4	Ford M2C134-D, CNH MAT 3525	John Deere J20C
Massey Ferguson M1135/M1141/M1143/M1145	Volvo WB 101	Allison C4
Cat TO-2	ZF TE-ML 03E/05F/06K	NH 410B
Case MS1205/MS1206/MS1207 (suitable for use)		

Typicals

Density at 15 °C, kg/l	0,883
Viscosity -20 °C, mPa.s	4800
Viscosity 40 °C, mm ² /s	67,00
Viscosity 100 °C, mm ² /s	10,70
Viscosity Index	147

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Flash Point COC, °C	225
Pour Point, °C	-35
Total Base Number, mgKOH/g	7,3
Sulphate Ash, %	1,19

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.