



Product Information 01.30.77

21-03-2014

Armado Synth LSP Ultra 10W-40

Description

Armado Synth LSP Ultra 10W-40 is a top-quality, fuel-saving diesel motor oil based on the latest additives technology, combined with very special base oils. As a result, this motor oil features the following properties:

- Very powerful dispersion and detergency
- Reduced tendency to form particulates: extends the service life of the particulate filter
- Very resistant to corrosion and foaming
- Naturally high viscosity index
- A low sulfate ash, phosphorus and sulfur content (Low-SAPS)
- Powerful wear resistance: resulting in reduced wear of piston rings and cylinder wall
- Reduced fuel consumption
- Contributes to a reduction in maintenance costs

Application

Armado Synth LSP Ultra 10W-40 is a fuel-saving lubricant oil, specially developed for diesel engines that are used in the most severe operating conditions in all seasons. This product is highly suitable for use in EURO 4, EURO 5 and EURO 6 engines in combination with diesel fuels with a low sulfur content. This motor oil is also suitable for use in engines with or without particulate filters and catalytic converters. This motor oil is part of the Low SAPS group of lubricants.

Specifications

ACEA E4/E6/E7/E9	API CJ-4	Volvo VDS-4, Renault VI RLD-3
MB-Approval 228.31/228.51	MAN M 3477/M 3575/M 3271-1	MTU Type 3.1
Mack EO-O Premium Plus	Deutz DQC IV-10 LA	Cat ECF-3, Cummins CES 20081
Detroit Diesel 93K218		

Typicals

Density at 15 °C, kg/l	0,864
Viscosity -25 °C, mPa.s	6600
Viscosity 40 °C, mm ² /s	92,90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Viscosity 100 °C, mm ² /s	14,00
Viscosity Index	154
Flash Point COC, °C	225
Pour Point, °C	-33
Total Base Number, mgKOH/g	12,8

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.