



Product Information 01.30.79

21-03-2014

Armado Synth LSP Ultra 5W-30

Description

Armado Synth LSP Ultra 5W-30 is a top quality fuel economy diesel engine oil based on the latest additive technology combined with very special base oils. This engine oil has the following properties:

- Very powerful detergency prevents deposits in the engine
- Very strong dispersion that prevents from precipitation and sludge
- A powerful activity against wear, corrosion and foam
- A high and stable viscosity index
- A low sulphated ash number
- Prolonged oil drain intervals
- A lower fuel consumption

Application

Armado Synth LSP Ultra 5W-30 has mainly been developed for heavy diesel engines even under the toughest operation conditions and all the year round. This product is very suitable for EURO 4, EURO 5 and EURO 6 engines in combination with diesel fuel with a low sulphur content. This engine oil is also suitable for application in engines with or without particle filters and exhaust catalyts. This motor oil is one of the group Low SAPS lubricants.

Specifications

ACEA E6/E7/E9	API CJ-4/SN	MB-Approval 228.31/228.51
MAN M 3677/M 3477/M 3271-1	Volvo VDS-4/VDS-3	Mack EO-O Premium Plus/EO-N
Renault VI RLD-3/RLD-2	Meets the requirements of	MTU Type 3.1
Renault VI RXD/RGD	Mack EO-M Plus	Cummins CES 20081, Cat ECF-3
Deutz DQC IV-10 LA, JASO DH-2		

Typicals

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6460
Viscosity 40 °C, mm ² /s	70,20

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Viscosity 100 °C, mm ² /s	11,80
Viscosity Index	165
Flash Point COC, °C	214
Pour Point, °C	-45
Total Base Number, mgKOH/g	9,3

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.