



## Product Information 06.10.20

21-03-2014

### Chainlube XS 100

#### Description

Chainlube XS 100 is based on premium, low-aromatic base oils, supplemented with a special package of additives in order to achieve the following properties:

- Excellent adhesion to the chain, as a result of which oil does not fly off the chain
- Outstanding lubricating properties

#### Application

Chainlube XS 100 has been specially developed to lubricate the cutting chain on a chainsaw so that it will not jam or break. Chainlube XS 100 is NOT suitable for lubricating the drive engine.

#### Typicals

Density at 15 °C, kg/l	0,883
Viscosity 40 °C, mm <sup>2</sup> /s	100,00
Viscosity 100 °C, mm <sup>2</sup> /s	11,30
Viscosity Index	98
Flash Point COC, °C	230
Pour Point, °C	-25

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.