



Product Information 01.20.60

21-03-2014

Dieselfleet CD+ 15W-40

Description

Dieselfleet CD+ 15W-40 is a motor oil for the latest generation of diesel engines, based on premium solvent-refined base oils, supplemented with carefully balanced additives. Dieselfleet CD+ 15W-40 features the following properties:

- Very powerful detergency, thereby reducing deposits in the hot zone of the engine to a minimum
- Very powerful dispersion, which acts to prevent formation of sediment and sludge
- Very resistant to corrosion and foaming
- A high and stable viscosity index
- A low ash content
- Highly effective against wear, resulting in reduced wear of piston rings and cylinder wall

Application

Dieselfleet CD+ 15W-40 is a motor oil suitable for diesel engines both with and without turbochargers, that are used under the most severe operating conditions in all seasons. Dieselfleet CD+ 15W-40 has a high 'Total Base Number' and is thus also suitable for use with fuels with a relatively high sulfur content. This motor oil has been specially developed to facilitate long oil change intervals (45,000 km) and to prevent 'Bore Polishing' (cylinder wall wear).

Specifications

ACEA A3/B4, E7	API CI-4/SL	MB-Approval 228.3/229.1
Volvo VDS-3, RVI	Mack EO-N	Cummins CES
RLD/RLD-2		20076/20077/20078
MAN M 3275	Cat ECF-1-a/ECF-2	Deutz DQC III-10
Mack EO-M Plus	MTU Type 2	Global DHD-1

Typicals

Density at 15 °C, kg/l	0,885
Viscosity -20 °C, mPa.s	6300
Viscosity 40 °C, mm ² /s	110,30
Viscosity 100 °C, mm ² /s	14,50
Viscosity Index	135

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Flash Point COC, °C	212
Pour Point, °C	-35
Total Base Number, mgKOH/g	10,7
Acid number, mgKOH/g	4,33
Sulphate Ash, %	1,37

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.