



Product Information 01.50.10

21-03-2014

Kroontrak Super 10W-30

Description

Kroontrak Super 10W-30 is a modern multifunctional oil for use in agricultural and earth-moving machinery. The product is based on premium solvent-refined base oils with additives to achieve the following properties:

- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent EP properties
- A high and stable viscosity index

Application

Kroontrak Super 10W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for:

- Petrol engines
- Diesel engines and turbo diesels
- Transmissions, also for wet brakes
- Hydraulic systems

Specifications

API SF/CG-4/GL-4	ACEA E3	Meets the requirements of
Ford M2C159-C	Massey Ferguson	John Deere J27/20C
	M1139/M1144/M1145	
Ford M2C134-D	Massey Ferguson	ZF TE-ML 06B/07B
	M1135/M1143	
Allison C4	NH 410B	MB 227.1

Typicals

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	6200
Viscosity 40 °C, mm ² /s	66,30
Viscosity 100 °C, mm ² /s	10,40
Viscosity Index	144

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Flash Point COC, °C	220
Pour Point, °C	-40
Total Base Number, mgKOH/g	10,7
Sulphate Ash, %	1,45

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.