



Product Information 01.50.12

21-03-2014

Kroontrak Synth 10W-40

Description

Kroontrak Synth 10W-40 is a modern, semi-synthetic, multifunctional oil for use in agricultural and earth-moving machinery. Kroontrak Synth 10W-40 is based on premium solvent-refined and synthetic base oils, supplemented with the additives to achieve the following properties:

- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent 'Extreme Pressure' properties
- A high and stable viscosity index

Application

Kroontrak Synth 10W-40 is a multifunctional oil (*) to be used for the lubrication of:

- Petrol engines
- Diesel engines (and turbo diesels)
- Transmissions (also for wet brakes)
- Hydraulic systems (*) Super Tractor Oil Universal = STOU

Specifications

API SF/CG-4/GL-4	ACEA E3	Massey Ferguson M1144/M1145
Ford M2C134-D ZF TE-ML 06B/07B	John Deere J20C Allison C4	Massey Ferguson M1143 MB 227.1

Typicals

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	6400
Viscosity 40 °C, mm ² /s	88,40
Viscosity 100 °C, mm ² /s	13,60
Viscosity Index	156
Flash Point COC, °C	220
Pour Point, °C	-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Total Base Number, mgKOH/g	10,9
Sulphate Ash, %	1,45

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.