



Product Information 02.35.00

21-03-2014

SP Matic 2012

Description

SP Matic 2012 is a premium, synthetic automatic transmission oil. By using premium base oils and additives, the following properties are achieved:

- Very low viscosity: ensures that gear-changing is effective and smooth, even at low temperatures
- Excellent oxidation stability: good resistance to the current, long oil change intervals
- A low pour point
- Excellent resistance to corrosion, wear and foaming: optimal protection of the transmission
- Does not affect seals used: prevents leakages

Application

SP Matic 2012 can be used in automatic transmissions, power steering systems, torque converters and other applications. Always consult the Kroon-Oil advisory database for optimal use.

Typicals

Colour	ROOD
Density at 15 °C, kg/l	0,859
Viscosity 40 °C, mm ² /s	35,90
Viscosity 100 °C, mm ² /s	7,86
Viscosity Index	199
Flash Point COC, °C	180
Pour Point, °C	-42
Pour Point, °C	<-40
Total Base Number, mgKOH/g	2,2
Sulphate Ash, %	0,06

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.