



Product Information 02.20.30

21-03-2014

Unigear GL3/GL5 80W-90

Description

Unigear HS GL3/GL5 80W-90 is a Total Drive Line transmission oil, primarily based on the best (PAO) synthetic base oils. Modern additives provide the product with the following properties:

- Excellent low temperature properties: easier gear-changing
- Very high resistance to rust, corrosion and foaming
- Premium 'Extreme Pressure' properties: limited wear
- Outstanding thermal stability and optimal lubrication for the entire (extended) oil change interval: long service life and optimal technical reliability, which should reduce the variable costs

Application

Unigear HS GL3/GL5 80W-90 is a universal transmission oil, specially developed for manual transmissions and differentials in cars and vans. This Total Drive Line transmission oil is highly suitable for workplaces in which a mixed vehicle fleet is maintained. Universally applicable where API GL-3, GL-4 and GL-5 is recommended in the viscosity class 80W-90.

Specifications

API GL-3/GL-4/GL-5/MT-1	Mil-L-2105A/B/C/D/E, Mil-PRF-2105E	DAF
MAN 341 Typ Z2/E2	Scania STO 1:0	ZF TE-ML 02B/05A/07A/08/12E
ZF TE-ML 16B/16C/16D/17B/19B/21A Iveco	MB 235.0	Mack GO-J

Typicals

Density at 15 °C, kg/l	0,883
Viscosity 40 °C, mm ² /s	125,80
Viscosity 100 °C, mm ² /s	15,00
Viscosity Index	122
Flash Point COC, °C	234
Pour Point, °C	-35

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.