



Product Information 02.10.35

21-03-2014

Unigear LS GL3/GL5 85W-140

Description

Unigear LS GL3/GL5 85W-140 is a universal 'Total Drive Line' transmission oil based on premium, solvent-refined base oils. It has been supplemented with special 'Extreme Pressure' additives to achieve the following properties:

- Outstanding resistance to high temperature loads
- Very high resistance to wear, corrosion and foaming
- Very special 'Extreme Pressure' properties
- Outstanding 'Limited Slip' properties
- A very broad field of application

Application

Unigear LS GL3/GL5 85W-140 is a 'Total Drive Line' transmission oil, developed for manual transmissions and differentials in cars, vans and heavy commercial vehicles. Unigear LS GL3/GL5 85W-140 is particularly suitable as a universal product for a wide range of applications. Furthermore, this oil has outstanding 'Limited Slip' properties.

Specifications

API GL-4/GL-5/MT-1	Mil-L-2105A/B/C/D/E, Mil-L-PRF-2105E	MAN 341 Typ Z2/E2, MAN 342 Typ M2
Scania STO 1:0	ZF TE-ML 05C/07A/08/12C/16E	

Typicals

Colour	4.5
Density at 15 °C, kg/l	0,905
Viscosity 40 °C, mm ² /s	345,80
Viscosity 100 °C, mm ² /s	26,10
Viscosity Index	99
Flash Point COC, °C	222
Pour Point, °C	-18

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.